Friedrich 35 and 50 Pint Capacity Dehumidifiers

3 OPTIONS FOR EASY DRAINAGE





THE EXPERTS IN ROOM AIR CONDITIONING

ELIMINATE EXCESS HUMIDITY AND MOISTURE THAT CAN RUIN CLOTHES AND FURNISHINGS, AND EFFECT YOUR HEALTH



Comfort & Convenience:

- Top-mount digital touch controls display room temperature and relative humidity level
- Set humidity level from 30% to 90% RH
- Low temperature operation to 41°F
- Removable condensate bucket with handle
- Washable, slide-out filter
- 24 hr. ON/OFF timer (timer must be set for each use-no memory)
- 2-speed fan
- Automatic defrost cycle
- Auto-restart
- Built-in casters for easy mobility
- 6 ft. power cord



Energy Efficiency:

- ENERGY STAR[®] models
- R-32 refrigerant with low Global Warming Potential
- \cdot Fan cycles off with the compressor

Sleek, Clean Modern Design

 Non-louvered front panel has a clean, stylish appearance that doesn't accumulate unsightly dust, pet hair and other household debris. Top mount digital controls





CONVENIENCE FEATURES FOR CAREFREE OPERATION

Three Ways to Drain:

- 1. Built-in drain pump that can pump condensation vertically or horizontally up to a combined distance of 15 feet. Intuitive drain pump operation senses condensate levels and begins draining process as needed. Unit will continue operating after emptying without any manual reset.
- 2. All models come with removable condensate bucket (16.2 pints capacity).
- 3. All models have **continuous drainage** outlet that accepts standard garden hose.



Built-in drain pump





Slide out condensate bucket

Continuous drain option

Dehumidifier Sizing Guide

Dehumidifier capacity is usually measured in pints per 24 hours and is determined by two factors:

- 1. The size of the space that needs to be dehumidified.
- 2. The conditions that exist in the space before dehumidification. Use the chart to estimate the capacity you need.

	SMALL TO MID-SIZE SPACE	MID-SIZE TO LARGE SPACE	
Room Conditions	100 - 1,000 sq. ft.	1,000 - 2,000 sq. ft.	
DAMP Area feels damp and has a musty odor only in humid weather	D35 (35 pint)		
VERY DAMP b Area always feels damp & has a musty odor & may exhibit damp spots on walls & floors	D35 (35 pint)		
WET A A Area always feels and smells wet and the walls & floors sweat or seepage is present	D35 (35 pint)	D50 (50 pint)	
EXTREMELY WET Area has wet floors or exhibits standing water	D35 (35 pint)	D50 (50 pint)	

SPECIFICATIONS

Model Number	D35B1B	D50B1B		
UPC	724587442403	724587442410		
ENERGY STAR®	Yes	Yes		
Dehumidification Capacity* (Pints/24 hrs)	35	50		
Built-in Drain Pump	Yes	Yes		
Drain Pump Hose (Length ft)	16' 9"	16' 9"		
Control	Digital	Digital		
Power	115V/60HZ	115V/60HZ		
Current (Amps)	5.2	8.2		
Watts	600	900		
Energy Factor (EF), L/kWh**	2.0	2.0		
Compressor Type	Rotary	Rotary		
Refrigerant Type / Charge amount (Oz)	R-32 / 8.8 Oz	R-32 / 10.9 Oz		
Operating Temperature Range	41°F- 90°F	41°F- 90°F		
Bucket Capacity (Pints)	16.2 approximate	16.2 approximate		
Easy Roll Casters	Yes-built in	Yes-built in		
Dimensions (WxHxD)	15" x 23 ¹ /4" x 12"			
Net/Shipping Weight	40.0/45.9	44.3/48.9		
Carton Dimensions (WxHxD)	mensions (WxHxD) 16 ¹ /4" x 24 ³ /4" x 13 ³			

POWER CORD/PLUG TYPE

Model	Circuit Rating Breaker or T-D Fuse	Plug Face (NEMA)	Wall Outlet Appearance	Power Cord Length
All models	125V-15A	5-15P		6 FT.

*The rating is expressed in pints per 24 hour period.

**Energy Factor: The energy efficiency of dehumidifiers is measured by its energy factor, in liters of water removed per kilowatt-hour (kWh) of energy consumed or L/kWh. In general, a higher energy factor means a more efficient dehumidifier. As an ENERGY STAR® partner, Friedrich Air Conditioning Co. has determined that the selected ENERGY STAR® models meet the ENERGY STAR® guidelines for energy efficiency.

One year limited warranty on parts and labor; five years on the sealed refrigeration system.

Due to continuing research in new energy-saving technology, specifications are subject to change without notice.



